## **BXBW Belspray**

## drum-lift motorised wheeled sprayer for cold bitumen emulsion

Contact: Sales at BX Plant on +44 (0) 1243 781970 or email: <u>rhodge@bxplant.com</u> 9 Little London, Chichester, West Sussex PO19 1PH, UK



## Specification of **BXBW Belspray**

## direct-from-drum motorised sprayer for cold bitumen emulsion

- **Chassis:** Strong Arm drum-lift chassis comprising : Frame made from 3mm all tube; 2 No.16 x 4 pneumatic wheels with brake; 260 x 85mm swivel castor wheel; safety catch to handle; 60 x 6mm drum strap.
- **Pump:** Albany gear-type pump with relief valve set at 65psi. Filter fitted on inlet.
- **Engine:** Briggs & Stratton Intek or Honda GX120/160 petrol engine with 6:1 reduction box direct coupled to pump. Yanmar diesel with electric start also available.
- Suction: Suction pipe with strainer 1.2m long; 25mm flexible suction hose -1.8m long.
- **Hose:** 13mm dia bore oil delivery hose, 5m long with hose fittings.
- Lance: 13mm dia bore galvanised steel spray lance 2m long with handle, control valve and brass spray jet.
- **Spray rate:** 20 to 25 litres per minute depending on the grade of bitumen used and the speed of the operator.
- **Emulsion:** Suitable for cold bitumen emulsion Grade K1-40 & K1-60.
- Shipping: Dimensions 1530 x 1000 x 740mm.
- Net weight: Packed weight in cardboard box: 120kgs.
- Tariff No: 8424.20000