

## Specification of Belspray direct-from-drum motorised sprayer for concrete cure: **BSCP, -H: Pump Unit with Petrol Engine** **BSCP-DE: Pump Unit with Diesel Engine**

### Technical Information

Drawing No:

Chassis	Tubular frame with wire mesh cover fitted with 4 No rubber feet
Pump	Albany crown gear type pump with relief valve set at 65 psi.
Plumbing	A filter is fitted on the inlet plumbing. A three-way valve is fitted on the outlet plumbing to allow for re-circulation and agitation of the material in the drum.
Engine: Petrol ( <b>BSCP, -H</b> )	<b>Honda GX120HX</b> engine with 6:1 reduction gear box direct coupled to pump. Also available with a Briggs & Stratton engine
Engine: Diesel ( <b>BSCP-DE</b> )	<b>Hatz IB20-X</b> engine with 6:1 reduction gear box direct coupled to pump.
Suction pipe	Duplex suction pipe 1 metre long fitted with 8mm agitator jet.. Suction hose, 2 x 13mm hose; each 1.8 metres long.
Delivery hose	Hose assembly; 5 metres x 13mm dia bore
Spray lance	Spray lance, 10mm dia bore x 3 metres with handle complete with brass spray jet.
Rate of spray	20 to 25 litres per minute depending on engine speed.
Concrete Cure Material	Aluminium based concrete cure material.

### Export Information

Shipping dimensions	1200 x 1000 x 700mm high
Weight	Packed on a pallet: 85kg gross weight Packed in wooden packing case: 100kg gross weight
Customs Tariff No	8424 8995

### BX Plant Limited

Company Regn. No. 3797166 - Registered Office and Works Address:

**11 Dukes Court, Bognor Road, Chichester, West Sussex PO19 8FX**  
**Tel: +44 (0) 1243 781970 Fax: +44 (0) 1243 533547**