

Specification of Belspray direct-from-drum motorised sprayer for concrete cure:

BSCW, -H: Wheeled with Petrol Engine (Classic)

Technical Information

Drawing No:

Chassis	Welded construction angle steel chassis with 25mm cranked axle to allow for use of drums in the vertical or horizontal position. Tubular steel handle Stove enamelled with 4 No. pneumatic tyred wheels 400 dia. fixed to axles.
Pump	Gear type pump with relief valve set at 65 psi.
Plumbing	A filter is fitted on the inlet plumbing. A three-way valve is fitted on the outlet plumbing to allow for re-circulation and agitation of the material in the drum.
Engine: Petrol (BSCW, -H)	Briggs & Stratton engine with 6:1 reduction gear box direct coupled to pump. Alternative petrol engines offered: • Honda GX120HX
Suction pipe	Duplex suction pipe 1 metre long fitted with 8mm agitator jet.. Suction hose, 2 x 13mm oil delivery hose; each 1.8 metres long.
Delivery hose	Oil delivery hose; 5 metres x 13mm dia bore.
Spray lance	Spray lance, 10mm dia bore x 3 metres with handle complete with brass spray jet.
Rate of spray	20 to 25 litres per minute depending on engine speed.
Concrete Cure Material	Aluminium based concrete cure material. Proseal and Proseal 90

Export Information

Shipping dimensions	1200 x 1000 x 700mm high
Weight	Gross weight including packaging <ul style="list-style-type: none"> • Packed in carton: 78 kg (70 kg net) • Packed on pallet: 85kg • Packed in wooden packing case: 100kg
Customs Tariff No	8424 8995

BX Plant Limited

Company Regn. No. 3797166 - Registered Office and Works Address:

11 Dukes Court, Bognor Road, Chichester, West Sussex PO19 8FX
Tel: +44 (0) 1243 781970 Fax: +44 (0) 1243 533547