

# BSBH205 Belspray

hand operated sprayer for cold bitumen emulsion

Contact: Sales at BX Plant on +44 (0) 1243 781970 or email: [rhodge@bxplant.com](mailto:rhodge@bxplant.com)  
9 Little London, Chichester, West Sussex PO19 1PH, UK



## Specification of Belspray

### direct-from-drum hand operated sprayer for cold bitumen emulsion

- Chassis:** Welded construction angle steel chassis with 25mm cranked axle to allow for use of drums in the vertical or horizontal position. Tubular galvanised steel handle.  
4 No. pneumatic tyred wheels 400 dia. fixed to axles.
- Pump:** Double diaphragm hand operated pump with air receiver to give uniform spray rate.
- Suction:** Suction pipe with strainer - 1.2m long; 25mm flexible suction hose -1.8m long.
- Lance:** 13mm dia bore galvanised steel spray lance 2m long with handle & control valve.
- Hose:** 13mm dia bore oil delivery hose, 5m long with hose fittings
- Spray rate:** 15 to 20 litres per minute depending on the grade of bitumen used and the speed of the operator.
- Emulsion:** Suitable for cold bitumen emulsion
- Shipping:** Dimensions 1150 x 870 x 670mm
- Net weight:** Packed weight in cardboard box: 59kgs
- Tariff No:** 8424.20000