

BSBW Belspray

classic motorised wheeled sprayer for cold bitumen emulsion

**Contact: Sales at BX Plant on +44 (0) 1243 781970 or email: rhodge@bxplant.com
9 Little London, Chichester, West Sussex PO19 1PH, UK**



Specification of BSBW Belspray **direct-from-drum motorised sprayer for cold bitumen emulsion**

- Chassis:** Welded construction angle steel chassis with 25mm cranked axle to allow for use of drums in the vertical or horizontal position. Tubular galvanised steel handle. 4 No. pneumatic tyred wheels 400 dia. fixed to axles.
- Pump:** Albany gear-type pump with relief valve set at 65psi. Filter fitted on inlet.
- Engine:** Briggs & Stratton Intek or Honda GX120/160 petrol engine with 6:1 reduction box direct coupled to pump.
- Suction:** Suction pipe with strainer - 1.2m long; 25mm flexible suction hose -1.8m long..
- Hose:** 13mm dia bore oil delivery hose, 5m long with hose fittings.
- Lance:** 13mm dia bore galvanised steel spray lance 2m long with handle, control valve and brass spray jet.
- Spray rate:** 20 to 25 litres per minute depending on the grade of bitumen used and the speed of the operator.
- Emulsion:** Suitable for cold bitumen emulsion - Grade K1-40 & K1-60
- Shipping:** Dimensions 1150 x 870 x 670mm
- Net weight:** Packed weight in cardboard box: 78kgs
- Tariff No:** 8424.20000